

OCT 20
RAP650A

HITCH PINS, LOCKS & ACCESSORIES

All Mister Hitches hitch pins are made from S235JR/Q235B carbon steel. The Tensile strength is 375MPa & Yield strength is 235MPa. This is equivalent to a grade 4.6 bolt or dowel pin which has a "Single Shear strength" of 50Kn (5,099kg) and a "Double shear strength" of 100Kn (10,197kg). When the pin is used in a tow bar hitch receiver situation the "Double Shear" value applies. The Mister Hitches team have put together what is considered one of the best Hitch Pin programs on the Australian Market. The range consists of hitch locking and standard pins in both long and standard useable lengths, Anti-Rattle hitch pin locks, "Keyed Alike" hitch pin locks, coupling padlocks, R-clips Etc.

All Mister Hitches locking hitch pins have our exclusive "Push to Lock" security function which allows the user to lock the head onto the pin without the need of the key.



MহারHP
Anti-rattle Locking Hitch Pin
70mm Useable Length



MHPL2
Locking Hitch Pin Dog Bone Style
70mm Useable Length



MHPL2-2
Locking Hitch Pin Set of 2
"Keyed Alike" Dog Bone Style
70mm Useable Length



MHPL8
Locking Hitch Pin Long "J" Style
95mm Useable Length



MHPL6
Locking Hitch Pin Long Style Double
Security Electro-coat Finish
66/80/100mm Useable Lengths With
R-Clip Push To Lock Function



MHPL5
Locking Hitch Pin Dog
Bone Style
79mm Useable Length



MHPH4B
"Quick Fit" Hitch Pin Style
95mm Useable Length



MHP3
Hitch Pin Long Style
65/80mm Useable Lengths
10,000kg Double Shear



MHTPCL
Treg Pin & Coupler Pin Lock
Use with Treg/Trigg Poly Block
Pins & Snap On Couplings.
Gold Zinc Plated.



MHRC-3
3 Pack of Comfort Grip Hitch
Pin "R" Clips Zinc Plated with
Soft Vinyl Grip

MHP3 & MHTPCL also available in bulk (NHP3 & NOCL4)

*Manufacturers Names used for reference purposes only.